



BUILDING INSPECTIONS DEPARTMENT
 PO BOX 950, 209 SEMINARY ST.
 KENANSVILLE, NC 28349
 PHONE: (910) 296-2124 FAX: (910) 296-2166
 EMAIL: INSPECTIONS@DUPLINCOUNTYNC.COM

AFFIDAVIT FOR RESIDENTIAL SWIMMING POOLS, SPAS, AND HOT TUBS

I, _____ Owner's name (print please)

Project address: _____

I will need a safety barrier installed in accordance with the NC State Residential Building Code and all inspection approvals, including final inspection, will be obtained. The NC State Residential Building Code requires private pools to be enclosed by a barrier meeting the requirements of Appendix G. Residential Swimming Pools, Spas, and Hot tubs with permit applications filed after January 1, 2008 must meet at least one of the pool safety barrier requirements (please see options listed below.)

Indicate your method of compliance by checking the appropriate answer(s).

- The pool will be equipped with a powered safety cover in compliance with ASTM F-1346.
- The pool will be equipped with an approval safety pool cover complying with ASTM-F1346.
- The pool will be isolated from access from the dwelling and yard by an enclosure meeting the barrier requirements of Residential Code.
- Combination of a partial barrier, wall of dwelling serving as a partial barrier, alarms and/or self closing/latching devices:
- All doors and windows providing direct access from the home to the pool shall be equipped with an exit alarm complying with UL 2017 that has a minimum sound pressure rating of 85 dB A at 10 feet. The exit alarm shall produce a continuous audible warning when the door and its screen are opened. The alarm shall sound immediately after the door is opened and be with a manual means to temporarily deactivate the alarm for a single opening. Such deactivation shall last no more than 15 seconds. The deactivation switch shall be located at least 54 inches above the threshold of the door. Separate alarms are not required for each door or window if sensors wired to a central alarm sound when the contract is broken at any opening.
- All doors providing direct access from the dwelling to the pool must be equipped with a self-closing, self-latching device with mechanical latching/locking installed a minimum of 54 inches above the threshold, which is acceptable to the authority having jurisdiction so long as the degree of protection afforded is not less than the afforded protection described above.
- The pool or spa shall be designed to produce circulation throughout the area. Suction outlets shall be provided with a cover that confirms with ANSI/ASME A1 12.19.8M, or a 12" drain grate or larger, or an approved channel drain system (exception of surface skimmers). All outlet circulation systems shall be equipped with atmospheric vacuum relief. The pump circulation systems shall be provided with a minimum of (2) two suction outlets. A minimum of (3) three feet horizontal or vertical distance shall separate such outlets. These suction outlets shall be piped so that water is drawn through them dwelling simultaneously through a vacuum relief protected line to the pump or pumps. Inspection access to the interior of the dwelling is required if alarms on windows & doors or if its self closing/self latching doors are utilized to meet the above requirement.

Signature (Owner)

Witness (Signature)

Date

Date

Signature (Contactor)

Date

I, _____, a Notary Public for _____ County and the State of _____,
do hereby certify that _____,

personally appeared before me this date and acknowledged the due execution of the foregoing instrument. Witness my hand and official seal, this the _____ day of _____, 20 _____.

Notary Public Signature (seal)

My Commission Expires _____